

Washington, DC

THE GEORGE WASHINGTON UNIVERSITY

WASHINGTON, DC

Gensler

2020 K Street, Northwest Suite 200 Washington DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587

Seal/Signature

Date

12/31/2012

Project Name

SITE 75A

ZC Case # 06-11G/06-12G

Project Number


09.7075.000


Description


BLOCK SECTIONS

Scale

As indicated







SECTION- E/W

Washington, DC

THE GEORGE WASHINGTON UNIVERSITY

WASHINGTON, DC

Gensler

2020 K Street, Northwest Suite 200

Washington DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587

| Seal/Signature

Date

12/31/2012

Project Name

SITE 75A

ZC Case #

Project Number

09.7075.000

06-11G/06-12G

Description

LEED SCORECARD

Scale

12" = 1'-0"

A-600© 2011 Gensler

LEED CS 2009 (BD&C) - Summary Scorecard - SQ 75

SITE 75A

20037 LEED Goal: Gold LEED TBD - 09.70075.000



Gensler

			Documentation				
	Identifier	Credit Name	by:	Υ	MY	MN	N
	SSp1	Construction Activity Pollution Prevention	Contractor	R			
	SSc1	Site Selection	Client	1			
	SSc2	Development Density and Community Connectivity	Gensler	5			
8	SSc3 SSc4.1	Brownfield Redevelopment	Client				1
2	SSc4.1	Alternative Transportation - Public Transportation Access	Gensler	6			
S	SSc4.2	Alternative Transportation - Bicycle Storage and Changing Rooms	Client	2			
Sites	SSc4.3	Alternative Transportation - Low-Emitting and Fuel-Efficient Vehicles	Client	3			
	SSc4.4	Alternative Transportation - Parking Capacity	Gensler		2		
ble	SSc5.1	Site Development - Protect or Restore Habitat	Civil	1			
na	SSc5.2	Site Development - Maximize Open Space	Civil	1			
·Е	SSc6.1	Storm water Design - Quantity Control	Civil	1			
ıst	SSc5.2 SSc6.1 SSc6.2 SSc7.1	Storm water Design - Quality Control	Civil	1			
S	SSc7.1	Heat Island Effect - Non-roof	Civil	1			
	SSc7.2	Heat Island Effect - Roof	Gensler	1			
	SSc8	Light Pollution Reduction	MEP				1
	SSc9	Tenant Design and Construction Guidelines	Client	1			

				_	$\overline{}$	
Water (1	WEc3c	Water Use Reduction - 40%	MEP	1		
		Water Use Reduction - 35%	MEP	1		
	WEc3a	Water Use Reduction - 30%	MEP	2		
	WEc2 WEc3a	Innovative Wastewater Techologies	MEP		2	
		Water-Efficient Landscaping - Reduce by 100%	Landscape Des	2		
	WEc1a	Water-Efficient Landscaping - Reduce by 50%	Landscape Des	2		
	WEp1	Water Use Reduction	MEP	R		

EAp1 EAp2	Fundamental Commissioning of Building Energy Systems Commissioning Minimum Energy Performance Energy Modele				+
EAp2	Fundamental Refrigerant Management MEP	R			+
EAc1	Optimize Energy Performance MEP	6	2	0	
EAc1a	Optimize Energy Performance (12% New / 8% Renovation) MEP	3		- 0	۰
EAc1b	Optimize Energy Performance (12% New / 10% Renovation) MEP	1			+
EAC1C	Optimize Energy Performance (14% New / 10% Renovation) MEP	1			+
EAc1d	Optimize Energy Performance (18% New / 12% Renovation) MEP	1			+
EAc1e	Optimize Energy Performance (20% New / 16% Renovation) MEP		1		+
EAc1f	Optimize Energy Performance (22% New / 18% Renovation) MEP		1		+
EAc1g	Optimize Energy Performance (22% New / 10% Renovation) MEP				+
EAc1h	Optimize Energy Performance (26% New / 22% Renovation) MEP				+
EAc1i	Optimize Energy Performance (28% New / 24% Renovation) MEP				+
EAc1i	Optimize Energy Performance (30% New / 26% Renovation) MEP				+
EAc1k	Optimize Energy Performance (32% New / 28% Renovation) MEP				
EAc1l	Optimize Energy Performance (32% New / 26% Renovation) MEP MEP				
EAc1m	Optimize Energy Performance (36% New / 32% Renovation) MEP				
EAc1n	Optimize Energy Performance (38% New / 32% Renovation) MEP				
EAc10	Optimize Energy Performance (40% New / 36% Renovation) MEP				
EAc1p	Optimize Energy Performance (42% New / 38% Renovation) MEP				
EAc1q	Optimize Energy Performance (42% New / 30% Renovation) MEP				
EAc1r	Optimize Energy Performance (45% New / 42% Renovation) MEP				
EAc1s	Optimize Energy Performance (48% New / 44% Renovation) MEP				
EAc2	On-Site Renewable Energy MEP				
EAc3	Enhanced Commissioning Commissioning	2			+
EAc4	Enhanced Refrigerant Management MEP	2			+
EAc5.1	Measurement and Verification - Base Building MEP	3			+
EAc5.2	Measurement and Verification - Tenant Submetering MEP	3			+
EAc6	Green Power Client	2			+

		Documentatio				
Identifier	Credit Name	n by:	Υ	MY	MN	N
MRp1	Storage and Collection of Recyclables	Gensler	R			
MRc1.1a	Maintain Interior Nonstructural Components (25% Reuse)	Gensler				1
MRc1.1b	Maintain Interior Nonstructural Components (33% Reuse)	Gensler				1
MRc1.1c	Maintain Interior Nonstructural Components (42% Reuse)	Gensler				1
MRc1.1d	Maintain Interior Nonstructural Components (50% Reuse)	Gensler				1
MRc1.1e	Maintain Interior Nonstructural Components (75% Reuse)	Gensler				1
MRc2a	Construction Waste Management Divert 50% from Disposal	Contractor	1			
MRc2b	Construction Waste Management Divert 75% from Disposal	Contractor	1			
VIRc3	Materials Reuse - 5% Reuse	Contractor				1
MRc4a	Recycled Content - 10% of Content	Contractor	1			
VIRc4b	Recycled Content - 20% of Content	Contractor		1		
MRc5a	Regional Materials - 10% Manufactured	Contractor	1			
MRc5b	Regional Materials - 20% Manufactured + Extracted	Contractor		1		
MRc6	Certified Wood -50% FSC	Contractor	1			
		-	5	2		

			7	2	2	
IEQc8.2	Daylight and Views - Views for 90% of Seated Spaces	Gensler		1		
IEQc8.1	Daylight and Views - Daylight 75% of Spaces	Gensler			1	
IEQc7.1	Thermal Comfort - Design	MEP	1			
IEQc6.2	Controllability of Systems - Thermal Comfort	MEP/Architect				1
IEQc5	Indoor Chemical and Pollutant Source Control	MEP		1		
IEQc4.4	Low-Emitting Materials - Composite Wood and Agrifiber Products	Contractor	1			
IEQc4.3	Low-Emitting Materials - Flooring Systems (GreenLabel Plus, FloorSco	Contractor	1			
IEQc4.2	Low-Emitting Materials - Paints and Coatings	Contractor	1			
IEQc4.1	Low-Emitting Materials - Adhesives and Sealants	Contractor	1			
IEQc3.1	Indoor Air Quality Management Plan - During Construction	Contractor	1			
IEQc2	Increased Ventilation	MEP			1	
IEQc1	Outdoor Air Delivery Monitoring	MEP	1			
IEQp2	Environmental Tobacco Smoke (ETS) Control	Macerich	R			
IEQp1	Minimum Indoor Air Quality Performance	MEP	R			

=		Green Housekeeping	Client	1			
	IDc1.2	Integrated Landscape Management	Client	1			
	IDc1.3	Integrated Pest Management	Client	1			
ä		Low Mercury Bulbs	MEP	1			
nov	IDc1.5	Exemplary Performance - Public Transit Access	Gensler	1			
	IDalt1	Green Education	Client	0	0	0	0
	IDalt2	LEED EBOM	MEP	0	0	0	0
	IDc2	LEED® Accredited Professional	Gensler	1			
	Note: Each pro	eject may access a maximum of 3 exemplary performance credits.		6			

4	I	jess may access a manimum of a snamplany polycomanics of canal		-			
7	RPc1	SSc5.1	Civil	1			
Ja	RPc2	SSc6.1	Civil	1			
egior	RPc3	WEc2	MEP			1	
	RPc4	EAc1o	MEP	0	0	0	1
	RPc5	EAc2	MEP	0	0	0	1
	RPc6	MRc1.1e	Gensler				1

Note: Each project may access a maximum of 4 regional priority credits, selecting from the 6 availar 2 1

Project Totals 70 8 5

THE 2007 FOGGY BOTTOM CAMPUS PLAN COMMITS GW TO ACHIEVING THE EQUIVALENCY OF 16 POINTS, USING USGBC'S LEED V2.2 SCORECARD AS AN EVALUATOR OF THE SUSTAINABLE QUOTIENT OF A PROJECT. THIS SCORECARD REFLECTS GW'S ANTICIPATED GOAL OF SUBMITTING THIS PROJECT TO GBCI UNDER LEED-CS 2009 (BD&C) WITH A TARGET OF GOLD LEVEL CERTIFICATION

THIS SHEET INTENTIONALLY LEFT BLANK

SITE 75A

Washington, DC

THE GEORGE WASHINGTON UNIVERSITY

WASHINGTON, DC

Gensler

2020 K Street, Northwest Suite 200 Washington DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587

Seal/Signature

Date

12/31/2012

Project Name

SITE 75A

ZC Case #

06-11G/06-12G

Project Number 09.7075.000

Description

BLANK

Scale

A-601
© 2011 Gensler



Washington, DC

THE GEORGE WASHINGTON UNIVERSITY

WASHINGTON, DC

Gensler

2020 K Street, Northwest Suite 200 Washington DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587

|Seal/Signature

Date

10/26/2012

Project Name

SITE 75A **ZC Case #**

06-11G/06-12G


Project Number 09.7075.000

Description


EXISTING CONDITIONS PLAN

Scale

C-1© 2011 Gensler



P:2011/042_GWU-2100Penn/CAD/ENG/_Sheets/PUD/C-1 EXISTING.dwg, 11/28/



DUST CONTROL NOTES:

- THE CONTRACTOR SHALL CONDUCT OPERATIONS AND MAINTAIN THE PROJECT SITE AS TO MINIMIZE THE CREATION AND DISPERSION OF DUST. DUST CONTROL SHALL BE USED THROUGHOUT THE WORK AT THE SITE.
- 2. THE CONTRACTOR MUST PROVIDE CLEAN WATER, FREE FROM SALT, OIL AND OTHER DELETERIOUS MATERIAL TO BE USED FOR ON-SITE DUST CONTROL.
- 3. THE CONTRACTOR SHALL SUPPLY WATER SPRAYING EQUIPMENT CAPABLE OF ACCESSING ALL WORK AREAS.
- 4. THE CONTRACTOR SHALL IMPLEMENT STRICT DUST CONTROL MEASURES DURING ACTIVE CONSTRUCTION PERIODS ON-SITE. THESE CONTROL MEASURES WILL GENERALLY CONSIST OF WATER APPLICATIONS THAT SHALL BE APPLIED A MINIMUM OF ONCE PER DAY DURING DRY WEATHER OR MORE OFTEN AS REQUIRED TO PREVENT DUST EMISSIONS.
- FOR WATER APPLICATION TO UNDISTURBED SOIL SURFACES, THE CONTRACTOR SHALL:
 A APPLY WATER WITH EQUIPMENT CONSISTING OF TANK, SPRAY BAR, PUMP WITH DISCHARGE PERSURE CALIFE:
- DISCHARGE PRESSURE GAUGE;
 B. ARRANGE SPRAY BAR HEIGHT, NOZZLE SPACING AND SPRAY PATTERN TO PROVIDE
- COMPLETE COVERAGE OF GROUND WITH WATER; C. DISPERSE WATER THROUGH NOZZLES ON SPRAY BAR AT 20 PSI (137.8 K PA) MINIMUM. KEEP AREAS DAMP WITHOUT CREATING NUISANCE CONDITIONS SUCH AS PONDING.
- FOR WATER APPLICATION TO SOIL SURFACES DURING DEMOLITION AND/OR EXCAVATION,
 THE CONTRACTOR SHALL:
- A. APPLY WATER WITH EQUIPMENT CONSISTING OF A TANK, PUMP WITH DISCHARGE GAUGE, HOSES AND MIST NOZZLES;

 B. LOCATE TANK AND SPRAYING EQUIPMENT SO THAT THE ENTIRE EXCAVATION AREA CAN
- B. LOCATE TANK AND SPRATING EQUIPMENT SO THAT THE ENTIRE EXCAVATION AREA CAN BE MISTED WITHOUT INTERFERING WITH DEMOLITION AND/OR EXCAVATION EQUIPMENT OR OPERATIONS. KEEP AREAS DAMP WITHOUT CREATING NUISANCE CONDITIONS SUCH AS PONDING.
- C. APPLY WATER SPRAY IN A MANNER TO PREVENT MOVEMENT OF SPRAY BEYOND SITE BOUNDARIES.

CONSTRUCTION AND STABILIZATION SEQUENCE:

- INSTALL SEDIMENT AND EROSION CONTROL MEASURES INCLUDING STABILIZED TREE PROTECTION, AND SILT FENCE AS INDICATED ON SHEET C1.03. SEE SHEET C1.08 FOR SEDIMENTATION AND EROSION CONTROL DETAILS.
 SEDIMENT CONTROL MEASURES SHALL BE INSPECTED AND APPROVED BY THE INSPECTOR.
- 2. SEDIMENT CONTROL MEASURES SHALL BE INSPECTED AND APPROVED BY THE INSPECTOR PRIOR TO COMMENCING ANY OTHER LAND DISTURBING ACTIVITIES.
- 3. REMOVE ITEMS AS INDICATED ON DEMOLITION PLAN.
- 4. INSTALL SITE IMPROVEMENTS AS INDICATED ON CONSTRUCTION DOCUMENTS FOR THE PROPOSED BUILDING.
- 5. AT THE COMPLETION OF CONSTRUCTION AND AFTER THE INSPECTOR'S APPROVAL, ALL TEMPORARY SEDIMENTATION AND EROSION CONTROL MEASURES SHALL BE REMOVED.

SEDIMENTATION EROSION CONTROL NOTE:

THE APPLICANT MUST NOTIFY THE DEPARTMENT OF HEALTH BY PHONE (202–535–2250) AT LEAST 24 HOURS PRIOR TO THE START OF GRADING ACTIVITY AND WITHIN (2) WEEKS AFTER COMPLETION OF PROJECT TO REQUEST INSPECTION. IF THERE IS NEED TO MAKE CHANGES OR MODIFICATIONS IN THE APPROVED DESIGN, DEPARTMENT OF HEALTH MUST BE NOTIFIED IMMEDIATELY.

SCHEDULE AND HOLD PRE-CONSTRUCTION MEETING WITH THE SEDIMENT CONTROL INSPECTOR 48 HOURS PRIOR TO ANY LAND DISTURBING ACTIVITY. CALL 202-535-2977 FOR APPOINTMENT.

NOT

- THE CONTRACTOR SHALL BE RESPONSIBLE FOR DESIGN OF SHEETING AND SHORING AND SUPPORT OF EXISTING UTILITIES AND ADJACENT STRUCTURES. SHORING, BRACING, AND UNDERPINNING DESIGNED BY THE CONTRACTOR'S STRUCTURAL ENGINEER LICENSED IN THE DISTRICT OF COLUMBIA SHALL BE PROVIDED AS NECESSARY TO ENSURE THEIR SUPPORT.
- 2. PROVIDE SILT FENCE AT PERIMETER OF EXCAVATION AREA TO REMAIN IN PLACE UNTIL BELOW GRADE EXCAVATION HAS BEGUN UNLESS OTHERWISE APPROVED BY THE INSPECTOR.
- 3. CONTRACTOR TO PROVIDE ON SITE APPROVED STAMPED AND SIGNED SEDIMENTATION AND EROSION CONTROL DRAWINGS BY DEPARTMENT OF ENVIRONMENT WATERSHED PROTECTION DIVISION.
- 4. PROVIDE CHAIN LINK FENCE AT PERIMETER OF SITE.

CONSTRUCTION DATES:

- * THE PROPOSED DEMOLITION WORK DUE TO COMMENCE NO EARLIER THAN 2014 AND IS ANTICIPATED TO TAKE APPROXIMATELY 24 MONTHS.
- EXACT BEGINNING AND END OF CONSTRUCTION IS TO BE ESTABLISHED BY THE OWNER.

TOTAL AREA OF DISTURBANCE:

TOTAL AREA OF DISTURBANCE: 24,992 SQUARE FEET OR 0.5737 AC

TOTAL VOLUME OF CUT OF BELOW GRADE EXCAVATION:

TOTAL AREA OF EXCAVATION: 24,299.58 SF / 0.5578 AC VOLUME OF CUT: 24,299.58 SQ.FT. (AREA) X 31.50 FEET (DEPTH)

VOLUME OF CUT: 131,788.29 cy +/-

SEDIMENT CONTROL APPROVAL:

AN NUMBER:

PLAN NUMBER:
THIS APPROVAL IS FOR GRADING AND SEDIMENT CONTROL ONLY. PERMITTEE/ CONTRACTOR IS REQUIRED TO
CONSTRUCT DESIGN FEATURE. SHOWN HEREON. HE SHALL NOTIFY THIS OFFICE AT NUMBER LISTED BELOW AT
LEAST 24 HOURS BEFORE START OF GRADING ACTIVITY, AND WITHIN TWO WEEKS AFTER COMPLETION OF
PROJECT FOR FINAL INSPECTION.

EROSION AND SEDIMENT CONTROL BRANCH

FOR FURTHER INFORMATION, PLEASE CALL: GOVERNMENT OF THE DISTRICT OF COLUMBIA DISTRICT DEPARTMENT OF ENVIRONMENT WATERSHED PROTECTION DIVISION

1200 1ST-STREET, NE WASHINGTON, D.C. TEL NO. (202) 535-2240 FAX NO. (202) 535-1364 THIS SHEET IS TO BE USED FOR SEDIMENTATION AND EROSION CONTROL PURPOSES ONLY!!

TEMP CONSTRUCTION ENTRANCE

SILT FENCE

INLET PROTECTION

APPROXIMATE LIMIT

OF BELOW GRADE EXCAVATION

LIMIT OF DISTURBANCE

TREE PROTECTION

STRAW BALE DIKE

1" = 50'

(IP)

ST)

☐ (SBD)

SITE 75A

Washington, DC

THE GEORGE WASHINGTON UNIVERSITY

WASHINGTON, DO

Gensler

2020 K Street, Northwest Suite 200 Washington DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587

|Seal/Signature

Date

10/26/2012

Project Name

SITE 75A

ZC Case # 06-11G/06-12G

Project Number

Description

09.7075.000

SEDIMENTATION AND EROSION CONTROL PLAN

Scale

Washington, DC

THE GEORGE **WASHINGTON** UNIVERSITY

WASHINGTON, DC

Gensler

2020 K Street, Northwest

Suite 200
Washington DC 20006
Telephone 202.721.5200
Facsimile 202.872.8587

|Seal/Signature

Date

10/26/2012

Project Name

SITE 75A

∣ZC Case #


06-11G/06-12G


Project Number 09.7075.000

Description

SITE PLAN

Scale





Washington, DC

THE GEORGE **WASHINGTON** UNIVERSITY

WASHINGTON, DC

Gensler

2020 K Street, Northwest Suite 200 Washington DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587

|Seal/Signature

Date

10/26/2012

Project Name

SITE 75A

ZC Case #

06-11G/06-12G

Project Number

09.7075.000

Description UTILITY PLAN

Scale

Washington, DC

THE GEORGE WASHINGTON UNIVERSITY

WASHINGTON, DO

Gensler

2020 K Street, Northwest Suite 200

Washington DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587

|Seal/Signature

Date

10/26/2012

Project Name

SITE 75A

ZC Case #

06-11G/06-12G


Project Number 09.7075.000

Description

SEDIMENTATION AND EROSION CONTROL **DETAILS**

Scale

© 2011 Gensler



Soluriosative members of the contract of the c

DETAIL 4 - SILT FENCE 5' MAXIMUM CENTER TO PERSPECTIVE VIEW 36' MINIMUM FENCE POST LENGTH FILTER CLOTH FENCE POST SECTION MINIMUM 20' ABOVE GROUND TOP VIEW EMBED GEOTEXTILE CLASS F A MINIMUM OF 8' VERTICALLY
INTO THE GROUND STANDARD SYMBOL

Fence posts shall be a minimum of 36' long driven 16' minimum into the round. Wood posts shall be 11/2' x 11/2' square (minimum) cut, or 13/4' diame minimum) round and shall be of sound quality hardwood. Steel posts will be translard T or I section weighting not less than 1.00 pond per linear foot.

. Silt Fence shall be inspected after each rainfall event and maintained wh U.S. BEPARTMENT OF AGRICULTURE PAGE VATERSHED PROTECTION DIVISION NATURAL RESOURCE CONSERVATION SERVICE 9 - 5 - 3 DISTRICT OF COLUMBIA DEPARTMENT OF HEAL.

DETAIL 6A - STANDARD INLET PROTECTION EDGE OF ROADVAY OR OF EARTH DIKE STANDARD SYMBOL

2. By we the "' x " construction grade labeled posts 1" into the ground at each corner of the inits." Piace not is \$1\text{ps}\$ between the "Fire the "piace" and the "piace" and the "piace" and "

3. Stretch the 1/2' \times 1/2' wire mesh tightly around the frame and fasten securely. The ends must neet and overlap at a

6. Stretch the Geotextile Class E tightly over the wire mesh with the geotixtile extending from the top of the frame to 18° below th inter notch elevation. Fastern the geotextile firmly to the frame he ends of the geotextile nust neet at a post, be overlopped and olded, then fastered down.

Backfill around the inlet in compacted 6' layers until the layer of earth is level with the notch elevation on the ends and top elevation on the sides.

7. The structure must be inspected periodically and after each U.S. BEPARTMENT OF AGRICULTURE PAGE VATERSHED PROTECTION DIVISION ATURAL RESOURCE CONSERVATION SERVICE B - 7 - 5 DISTRICT OF COLUMBIA DEPARTMENT OF HEALTH

DETAIL 9 - FARTH DIKE

DETAIL 6B - AT GRADE INLET PROTECTION PLAN/CUT AWAY VIEW STANDARD SYMBOL CROSS SECTION


Lift grate and wrap with Geotextile Class E to completely cover all openings then set grate back in place.

CROSS SECTION

PLAN VIEW

STABILIZATION

PD/S-1 SEED AND MULCH (DRAINING & ACRE)
PD/S-2 SEED AND COVER WITH SOIL STABILIZATION MATTING OR LINE WITH SOD (DRAINING BETWEEN 1 AND 2 ACRES)



1. Attach a continuous piece of wire mesh (30° minimum width by throat length plus to the 2" \times 4" weir (measuring throat length plus 2') as shown on the standard

2. Place a continuous piece of Geotextile Class E the same dimensions as the wire mesh over the wire mesh and securely attach it to the 2^* x 4^* weir. Securely nail the 2" X 4" weir to a 9" long vertical spacer to be located between the weir and the inlet face (max. 4' apart).

5. The assembly shall be placed so that the end spacers are a minimum 1' beyond both ends of the throat opening.

6. Form the 1/2 " $\times 1/2$ " wire mesh and the geolexille fabric to the concrete gutter optimat the face of the curb on both sides of the inlet. Place clean 3/4" $\times 1/2$ " states over the wire mesh and geolexille in such a manner to prevent water from entering the inlet under or around the geolexille.

 This type of protection must be inspected frequently and the filter cloth and stone replaced when clogged with sediment. 8. Assure that storm flow does not bypass the inlet by installing a temporary earth or aspholt dike to direct the flow to the inlet.

PIPE DUTLET SEDIMENT TRAP - ST I

The structure shall be renoved and area stabilized when the drainage area has been properly stabilized.

8. All cut and fill slopes shall be 2:1 or flatter.

. All pipe connections shall be watertight.

11. The riser shall be wrapped with 1/2' hardware cloth (wire) then wrappe Geotextile Class E. The filter cloth shall extend 6' above the highest s and 6' below the lowest silt. Where ends of filter cloth cone together, they shall be overlopped. Folded and fastered to prevent bypass. Filter cloth shall be replaced as necessary to prevent clogging.

14. The riser shall be anchored with either a concrete base or stee base to prevent floatation. Concrete bases shall be at least twice the riser and the state of the riser base shall be at least twice the riser disaster. J'4" minima whichness attached to the botton of the riser by a continuous weld to form a vatertight correction. Then place 2" of stone, groval or tapped ea

17. Refer to Section G for dewatering requirements of sediment traps

D = DISTANCE BETVEEN INFLOW AND DUTFLOW

$$\label{eq:alpha} \begin{split} \mathbf{A} &= \mathbf{AREA} \ \mathbf{DF} \ \mathbf{PERMANENT} \ \mathbf{PDDL} \\ \mathbf{V_{e}} &= \mathbf{EFFECTIVE} \ \mathbf{VIDTH} \end{split}$$

FORMULA: We = (A/2)1/8

Le TOTAL DISTANCE FROM THE INFLOW POINT AROUND THE BAFFLES TO THE RISER

DETAIL 13 - STONE DUTLET SEDIMENT TRAP - ST II 1' HIN TOP OF EMBANKHENT TOP OF EMBANKENT WEIR LENGTH HEIGHT EXISTING GROUND TOP OF EMBANKENT 4' MAX. HEIGHT EXISTING GROUND SECTION B-B 4' MIN. WIDTH 4 MIN VIDEN MATERIAL STORE STORE STORE FLOW STORAGE F PERSPECTIVE VIEW SMALL RIP-RAP 4' TO 7' EXCAVATE FOR REQUIRED VET STORAGE SECTION A-A . Area under embankment shall be cleared, grubbed and stripped of my vegetation and root mat. The pool area shall be cleared.

The fill material for the embankment shall be free of roots and other woody vegetation as well as over-sized stones, rocks, organi material or other objectionable material. The embankment shall be compacted by traversing with equipment while it is being

4. The stone used in the outlet shall be small rip-rap 4' to 7' in size with a 1' thick layer of 3/4' to 11/2' washed aggregate placed in the state of the state of the state of the state of the stone state of the stone state of the stone facing by placing it on the inside face of the stone outlet.

U.S. DEPARTMENT OF AGRICULTURE PAGE WATERSHED PROTECTION DIVISION NATURAL RESOURCE CONSERVATION SERVICE D-14-11 DISTRICT OF COLUMBIA DEPARTMENT OF HEALT

STONE DUTLET SEDIMENT TRAP - ST II

The structure shall be inspected periodically and after each rain and repairs made as needed.

7. Construction of trops shall be carried out in such a monner that sediment pollution is aboted. Once constructed, the top and coulded fice of the embonament alm lab established with seed and coordinate with forder Stabilization Structure orients. The remainder of the inferior slopes shall be stabilized (one time) with seed and mulch upon top completion and mentioned and mentioned constructure.

The structure shall be dewatered by approved methods, removed and the area stabilized when the drainage area has been properly stabilized.

9. Refer to Section G for specifications concerning trap Minimum trap depth shall be measured from the weir elevation.

Outlet — An outlet shall be provided, including a means of conveying the discharge in an erosion free manner to an existing stable shared.

DETAIL 6E - AT GRADE INLET GUARD FILTER -STANDARD INLET GUARD ATTATCHMENT METHOD STANDARD INLET GUARD DIMENSIONS STANDARD INLET GUARD CROSS SECTION

CROSS SECTION

PERSPECTIVE VIEW

POSITIVE **

DETAIL 14 - RIP-RAP DUTLET SEDIMENT TRAP - ST III

TOP OF EMBANKMENT OR EXISTING GROUND

TRAP DISCHARGE
TO UNDISTURBED/
STABILIZED AREA

d d FLOW CROSS SECTION DIKE A DIKE B PLAN VIEW FLOW CHANNEL STABILIZATION GRADE 0.5% MIN. 10% MAX. All temporary earth dikes shall have uninterrupted positive grade to an outlet. Spot elevations may be necessary for grades less than 1%. Runoff diverted from a disturbed area shall be conveyed to a sediment trapping device.

3. Runoff diverted from an undisturbed area shall outlet directly into an undisturbed, stabilized area at a non-erosive velocity.

All trees, brush, stumps, obstructions, and other objectional material shall be removed and disposed of so as not to interfere with the proper functioning of the dike.

6. Fill shall be compacted by earth moving equipment.

All earth removed and not needed for construction shall be placed so that
it will not interfere with the functioning of the dike.

8. Inspection and maintenance must be provided periodically and after

U.S. BEPARTMENT OF AGRICULTURE PAGE VATERSHED PROTECTION DIVISION NATURAL RESOURCE CONSERVATION SERVICE C - 12 - 4 DISTRICT OF COLUMBIA DEPARTMENT OF HEALT

RIP-RAP DUTLET SEDIMENT TRAP - ST III

2. The fill naterial for the embankment shall be free of roots or other woody vegetation as well as over-sized stones, rocks, organic naterial or other objectionable naterial. The demokrace that libe compacted by troversing with equipment while it is being constructed. Maximum height of embankment shall be 4*, nessured at controlling of embankment.

3. All cut and fill slopes shall be 2:1 or flatter.

 Elevation of the top of any dike directing water into trap must equal or exceed the height of trap embankment. Storage area provided shall be figured by computing the volume measured from top of excavation. (For storage requirements see Table 12).

6. Filter cloth shall be placed over the botton and sides of the outlet channe prior to placement of stone. Section of fabric must overlap at least i' with section nearest the entrance placed on top. Fabric shall be embedded at least of into existing ground at entrance of outlet channel. 7. Stone used in the outlet channel shall be 4' - 12' placed 18' thick.

Dutlet - An outlet shall be provided, which includes a means of conveying the discharge in an erosion free manner to an existing stable channel. Protection against scoun at the discharge end shall be provided as necessary.

9. Dutlet channel must have positive drainage from the trap.

11. The structure shall be inspected periodically and after each rain and repaired as needed.

12. Construction of traps shall be carried out in such a manner that sediment pollution is abated. Direc constructed, the top and outside face of the enablancer shall be shall lized with seed and nuition. Points of concentrated infice shall be protected in accordance with Grade Stabilization Structure criteria. The renainder of the interior slopes should be stabilized (one time with seed and nuich upon trap completion and nontrored and naintained erosion free during the life of the trap.

DETAIL 12 - PIPE DUTLET SEDIMENT TRAP - ST I DETAIL 11 - PERIMETER DIKE / SWALE ALL SLOPES : PERSPECTIVE VIEW 4' MINIMUM TOP WIDTH - \Rightarrow PD/S-1 \Rightarrow GEDTEXTILE CLASS SE All perimeter dike/swoles shall have an uninterrupted positive grade to an outlet. Spot elevations may be necessary for grades less than 1% Runoff diverted from a disturbed area shall be conveyed to a sediment trapping device.

The area under the embankment shall be cleared, grubbed and stripped of any vegetation and root mat. The pool area shall be cleared. The fill material for the embankment shall be free of roots or other woody
vegetation as well as oversized stones, rocks, organic naterial, or other
objectionable naterial. The embankment shall be compacted by traversing
with equipment while it is being constructed.

DETAIL 74 - TREE PROTECTION

U.S. DEPARTMENT OF AGRICULTURE PAGE VATERSHED PROTECTION DIVISION NATURAL RESOURCE CONSERVATION SERVICE D = 14-7 DISTRICT OF COLUMBIA DEPARTMENT OF HEALTH

DETAIL 22 - SEDIMENT BASIN/TRAP BAFFLES INFLOV-




RISER CREST ELEVATION 6' (MINO ABOVE BAFFLE

DETAIL 34 - PORTABLE SEDIMENT TANK (HORIZONTAL)

BAFFLE DETAIL


 \triangle A 5" DIA. HOSE TO -SUITABLE OUTLET



DETAIL 35 - PORTABLE SEDIMENT TANK (VERTICAL)

3. Runoff diverted from an undisturbed area shall outlet into an undisturbed stabilized area at a non-erosive velocity.

Stabilization with seed and mulch or as specified of the area disturbed by the dike and swale shall be completed within 7 days upor



US. DEPARTMENT OF AGRICULTURE PAGE VATERAGED PROTECTION DIVISION
US. DEPARTMENT OF AGRICULTURE PAGE VATERAGED PROTECTION DIVISION
US. DEPARTMENT OF AGRICULTURE
US. DEPARTMENT OF AGRICULTURE

US. DEPARTMENT OF AGRICULTURE


ON TURBLE RESOURCE CONSERVATION SERVICE

G - 26 - 4


DISTRICT OF COLUMBIA DEPARTMENT OF HEALTH

NATURAL RESOURCE CONSERVATION SERVICE


G - 26 - 4





ELEVATION CROSS-SECTION A-A





NOTES:













SPECIFICATION FOR 5A ALLEY POLE:


WORK CONSISTS OF FURNISHING AND INSTALLING ALLEY LIGHT POLES AND LIGHT POLES PCC FOUNDATINS COMPLETE IN PLACE AT LOCATIONS SHOWN IN THE PLANS OR AS DIRECTED BY BY THE ENGINEER. LIGHT POLES SHALL BE DC TYPES SA WITH TAGGS FOR DC ID NAMBERS.

B) THE POLE SHALL BE 6.6 NOHES x 2.4 INCHES x 30 FT, TAPERED WITH A 3-FT ARM. THE POST SHALL INCLUDE A WELDED SIMPLEX TO ACCOMMODATE ONE 3-FT SINGLE MEMBER AND. THE SHAFT SHALL BE FABRICATED FROM 11-GAUGE STEEL MEETING ASTM-A595 OR A WIT A YELD POINT NO LESS THAN 50,000 PSI.

THE POST AND ARM SHALL BE HOT-DIP GALVANIZED PER THE REQUIREMENTS OF ASTM A123. THE POST AND AMR GALVANIZED COATING SHALL BE FREE OF ANY DEBRIS OR FLUX ASH. ALL GALVANIZED EXTERIOR SURFACES MISJALLY EXPOSED ARE TO BE S-FRED CONVECTION OVEN.







SITE 75A

Washington, DC

THE GEORGE **WASHINGTON** UNIVERSITY

WASHINGTON, DC

Gensler

2020 K Street, Northwest Suite 200 Washington DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587

Seal/Signature

Date

10/26/2012

Project Name SITE 75A

ZC Case # 06-11G/06-12G

Project Number 09.7075.000

Description

SITE DETAILS

Scale

Washington, DC

THE GEORGE WASHINGTON UNIVERSITY

WASHINGTON, DC

Gensler

2020 K Street, Northwest

Suite 200 Washington DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587

Seal/Signature

Date

10/26/2012

Project Name

SITE 75A

ZC Case #

06-11G/06-12G

Project Number 09.7075.000


Description

SITE PLAN


Scale

1"=50"

L-01




PENNSYLVANIA AVENUE, NW



NOTES:

- 1. STREETSCAPE DETAILS ARE SHOWN IN CONCEPT FOR ILLUSTRATIVE PURPOSES. THE FINAL DETAILS OF THE STREETSCAPE IMPROVEMENTS WILL BE SELECTED DURING DETAILED DESIGN PHASES OF WORK AND CONFORM WITH APPLICABLE DESIGN AND PERMITTING STANDARDS.
- 2. INTERIOR LAYOUTS ARE ILLUSTRATIVE ONLY AND SUBJECT TO CHANGE ON FINAL PLAN.
- 3. STRUCTURAL SOIL OR SIMILAR PRODUCT SHALL BE PLACED BELOW COBBLES AND CONCRETE SIDEWALK TO PROMOTE TREE GROWTH.





SITE 75A

Washington, DC

THE GEORGE WASHINGTON UNIVERSITY

WASHINGTON, DC

Gensler

2020 K Street, Northwest Suite 200 Washington DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587

Seal/Signature

Date

10/26/2012

Project Name SITE 75A

ZC Case #

06-11G/06-12G

Project Number 09.7075.000

Description

PENN. AVENUE SITE PLAN

Scale

1"=20'

L-02
© 2011 Gensler

Washington, DC

THE GEORGE WASHINGTON UNIVERSITY

WASHINGTON, DC

Gensler

2020 K Street, Northwest

Suite 200
Washington DC 20006
Telephone 202.721.5200
Facsimile 202.872.8587

|Seal/Signature

Date

10/26/2012

Project Name

SITE 75A

ZC Case #

06-11G/06-12G

Project Number

09.7075.000

Description


PENN. **AVENUE** SITE PLAN

Scale

1"=20'

L-03 © 2011 Gensler

THIS SHEET LEFT INTENTIONALLY BLANK



CONDOMINIUM DATED NOVEMBER 15, 2012.

L-04 © 2011 Gensler